

# easymount.

## **LAMINATING AND APPLICATOR SYSTEM**

#### **KEY FEATURES**

- Patented roll fed-applicator combination
- Patented unique hover technology.
- Swing-out arms for easier loading of laminate and film.
- Pneumatic air pressure
- 6m/20ft a minute
- 45mm/1.8" mounting thickness
- · Variable speed control
- · Foot pedal
- Reverse mode
- Multilingual control panel

#### **GREAT FOR USE IN**

- Sign makers
- · Print finishers

#### **IDEAL WHEN LAMINATING**

- Single banners
- Reel-to-reel laminates
- Posters, graphics and signs
- Mounting prints to boards
- · Pop-up displays
- Applying vinyls, tapes and adhesive films
- Outdoor signage

and many more...

### Easymount Hybrid, bringing something new to the table.



BRAND NEW multi-patented Easymount Hybrid laminator, with unique HOVER technology. Incorporating both a traditional roll-fed laminator and flatbed applicator. Giving benefits of both of these applications in one system.

your business.

- World's first laminator and applicator, all in one.
- Roll to Roll technology for long run, roll-fed laminating.
- Patented floating rollers, save time, and keep's boards in perfect condition.
- Modular design, Length from 1.5 meters to unlimited lengths. Configured to grow with

Specifications	Easymount Hybrid
Laminating Speed (m/ft/min)	6m/20ft
Max. Width (mm/inches)	1600mm/63"
Mounting Thickness (mm/inches)	45mm/1.8"
Roller Diameter (mm/inches)	130mm/5″
Laminating Temperature (°C/°F)	0-60°C/32-140°F
Pressure Adjustment	Pneumatic (Optional silent compressor or use an existing air supply)
Film Core (mm/inches)	77mm/3"
Power Supply AC (V–Hz)	220/240–50-60
Power Consumption (W)	1500
Overall Dimensions (mm/inches)	2200x2900x1500mm/87x114x59"(Main Unit)1530x2900x1500mm/87x114x60"(Modular Unit)
Gross Machine Weight	680kg(Main unit) / 520kg (Modular Unit)
	1 year

sales@vividamericas.com